



Greenshine New Energy
GS-LED-B6 30W 6500K
24 PCS CREE XTE LAMP 6500K 30W
24 PCS CREE XTE LAMP 6500K 30W

Horizontal Footcandles
Scale: 1 Inch = 10 Ft.
Light Loss Factor = 0.90
Lumens Per Lamp = N.A. (absolute photometry)
Luminaire Lumens = 2622
Mounting Height = 14.00 Ft
Maximum Calculated Value = 1.88 Fc
Arrangement: Single

PHOTOMETRIC FILENAME : IES_GREENSHINE_GS-LED-B6-30W 6500K - TYPE '

DESCRIPTIVE INFORMATION (From Photometric File)

Greenshine New Energy
GS-LED-B6 30W 6500K
24 PCS CREE XTE LAMP 6500K 30W
24 PCS CREE XTE LAMP 6500K 30W



TEMPLATE SPECIFICATION

Horizontal Footcandles
Scale: 1 Inch = 10 Ft.
Light Loss Factor = 0.90
Lumens Per Lamp = N.A. (absolute photometry)
Luminaire Lumens = 2622
Mounting Height = 14.00 Ft
Maximum Calculated Value = 1.88 Fc
Arrangement: Single

LUMINAIRE LAYOUT INFORMATION

| <u>#</u> | <u>X</u> | <u>Y</u> | <u>Z</u> | <u>Orient</u> | <u>Tilt</u> | <u>Roll</u> | <u>Spin</u> | <u>Tilt Correction</u> |
|----------|----------|----------|----------|---------------|-------------|-------------|-------------|------------------------|
| 1 | 0.00 | 0.00 | 14.00 | 0.00 | 0.00 | 0.00 | 0.00 | 1.00 |